



GCA 1515 L52 RC

Boiler BiLight Compact cu montaj deasupra chiuvetei



Informatii principale


- Panou de comanda functional si comod
- Montare simpla deasupra chiuvetei



Interrupator On/Off



Instalare deasupra
chiuvetei



Termostat reglabil



GCA 1515 L52 RC

Boiler BiLight Compact cu montaj deasupra chiuvetei

| Caracteristici tehnice | |
|--|-------------------------|
| Volum [L] | 15 L |
| Protectia vasului | Sticla ceramica |
| Tensiunea de alimentare [V/Hz] | 230V/50Hz |
| Putere nominala [W] | 1500 W |
| Presiunea de functionare a vasului [Mpa] | 0.8 MPa |
| Izolatie [mm] | 19 mm |
| Timpul de incalzire de la 15°C la 60°C | 35 min |
| Intrerupator On/ Off | Da |
| Termostat reglabil | Da |
| Anod de magneziu | Da |
| Anod tester | Nu |
| Supapa de siguranta | Da |
| Dimensiuni H/ l/ D [m] | 0.399 x 0.377 x 0.304 m |
| Greutate neta [kg] | 8.30 kg |
| Instalare | Deasupra chiuvetei |
| Clasa energetica | C |
| Garantie | n/a |
| Profil incarcare | XXS |
| Consum anual de energie (AEC) kWh | 625 |